

## Marine Rubbing Pro

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

<b>Product name</b>	: Marine Rubbing Pro
<b>UFI</b>	: UU30-30RC-N009-UGWA
<b>Product code</b>	: 43582
<b>Product description</b>	: Cleaner.
<b>Product type</b>	: Liquid.
<b>Other means of identification</b>	: Not available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Professional use

#### 1.3 Details of the supplier of the safety data sheet

Jotun A/S  
P.O.Box 2021  
3202 Sandefjord  
Norway

Tel: + 47 33 45 70 00  
Fax: +47 33 45 72 42  
E-mail: SDSJotun@jotun.no

#### 1.4 Emergency telephone number

Norwegian National Poison Centre: +47 22 59 13 00

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning.

**Hazard statements** : H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.

Marine Rubbing Pro

## SECTION 2: Hazards identification

### Precautionary statements

- General** : Not applicable.
- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P273 - Avoid release to the environment.
- Response** : P391 - Collect spillage.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazardous ingredients** : distillates (petroleum), hydrotreated middle alcohols, c9-11, ethoxylated
- Supplemental label elements** : EUH208 - Contains C(M)IT/MIT (3:1). May produce an allergic reaction.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
distillates (petroleum), hydrotreated middle	EC: 265-148-2 CAS: 64742-46-7 Index: 649-221-00-X	≥25 - ≤50	Acute Tox. 4, H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
alcohols, c9-11, ethoxylated	CAS: 68439-46-3	<3	Eye Dam. 1, H318	-	[1]
C(M)IT/MIT (3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5	[1]

Marine Rubbing Pro

## SECTION 3: Composition/information on ingredients

			Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071  <b>See Section 16 for                  the full text of the H                  statements declared                  above.</b>	mg/l Skin Corr. 1B, H314: $C \geq 0.6\%$ Skin Irrit. 2, H315: $0.06\% \leq C < 0.6\%$ Eye Dam. 1, H318: $C \geq 0.6\%$ Eye Irrit. 2, H319: $0.06\% \leq C < 0.6\%$ Skin Sens. 1, H317: $C \geq 0.0015\%$ M [Acute] = 100 M [Chronic] = 100
--	--	--	---	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

*Marine Rubbing Pro*

## SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

*Marine Rubbing Pro***SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidising agents, strong alkalis, strong acids.

**Additional information on storage conditions**

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

**Seveso Directive - Reporting thresholds****Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

See Technical Data Sheet / packaging for further information.

**7.3 Specific end use(s)**

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
distillates (petroleum), hydrotreated middle	<b>FOR-2011-12-06-1358 (Norway, 9/2018).</b> TWA: 1 mg/m <sup>3</sup> 8 hours. Form: mineral oil particles TWA: 50 mg/m <sup>3</sup> 8 hours. Form: Vapour

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures

*Marine Rubbing Pro***SECTION 8: Exposure controls/personal protection**

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
alcohols, c9-11, ethoxylated  C(M)IT/MIT (3:1)	DNEL	Long term Oral	25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	87 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	294 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	1250 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2080 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.09 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/kg bw/day	General population	Systemic

**PNECs**

No PNECs available

**8.2 Exposure controls**

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection****Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

## SECTION 8: Exposure controls/personal protection

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

### Gloves

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: butyl rubber (> 0.4 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Off-white.
- Odour** : Characteristic.
- Odour threshold** : Not applicable.
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : Lowest known value: 172 to 379°C (341.6 to 714.2°F)(distillates (petroleum), hydrotreated middle).
- Flammability** : Not applicable.
- Lower and upper explosion limit** : Not applicable.
- Flash point** : Closed cup: >100°C
- Auto-ignition temperature** : Lowest known value: 225°C (437°F) (distillates (petroleum), hydrotreated middle).
- Decomposition temperature** : Not available.
- pH** : 7
- Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Vapour pressure** : Not available.
- Evaporation rate** : Not available.
- Density** : 1.18 g/cm<sup>3</sup>
- Vapour density** : Not available.
- Explosive properties** : Not available.



*Marine Rubbing Pro***SECTION 9: Physical and chemical properties****Oxidising properties** : Not available.**Particle characteristics****Median particle size** : Not applicable.**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity****10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
alcohols, c9-11, ethoxylated C(M)IT/MIT (3:1)	LD50 Oral	Rat	1378 mg/kg	-
	LD50 Oral	Rat	53 mg/kg	-

**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Marine Rubbing Pro distillates (petroleum), hydrotreated middle C(M)IT/MIT (3:1)	N/A N/A 53	N/A N/A 50	N/A N/A N/A	36.8 11 0.5	N/A N/A N/A

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
alcohols, c9-11, ethoxylated	Eyes - Irritant	Mammal - species unspecified	-	-	-

**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
C(M)IT/MIT (3:1)	skin	Mammal - species unspecified	Sensitising

**Mutagenicity**

No known significant effects or critical hazards.

**Carcinogenicity**

No known significant effects or critical hazards.

**Reproductive toxicity****Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.



*Marine Rubbing Pro***SECTION 11: Toxicological information****Teratogenicity**

No known significant effects or critical hazards.

**Specific target organ toxicity (single exposure)**

Based on available data, the classification criteria are not met.

**Specific target organ toxicity (repeated exposure)**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Product/ingredient name	Result
distillates (petroleum), hydrotreated middle	ASPIRATION HAZARD - Category 1

**11.2 Information on other hazards****11.2.1 Endocrine disrupting properties**

Not available.

**11.2.2 Other information**

Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
distillates (petroleum), hydrotreated middle alcohols, c9-11, ethoxylated C(M)IT/MIT (3:1)	Acute LC50 1.13 mg/l	Fish	96 hours
	Acute EC50 7 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.048 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0.0052 mg/l	Algae - Skeletonema costatum	48 hours
	Acute EC50 0.1 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.22 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC 0.00064 mg/l	Algae - Skeletonema costatum	48 hours
	Chronic NOEC 0.0012 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.004 mg/l	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.098 mg/l	Fish - Oncorhynchus mykiss	28 days

**Conclusion/Summary** : This material is toxic to aquatic life with long lasting effects.**12.2 Persistence and degradability****Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
C(M)IT/MIT (3:1)	-	-	Not readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
C(M)IT/MIT (3:1)	-	3.16	low

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.

*Marine Rubbing Pro***SECTION 12: Ecological information****12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties**

Not available.

**12.7 Other adverse effects**

No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** :  Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**European waste catalogue (EWC)**

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
20 01 29*	detergents containing hazardous substances

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.





**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

Marine Rubbing Pro

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	UN3082	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. (distillates (petroleum), hydrotreated middle)	Environmentally hazardous substance, liquid, n.o.s. (distillates (petroleum), hydrotreated middle)	Environmentally hazardous substance, liquid, n.o.s. (distillates (petroleum), hydrotreated middle). Marine pollutant (distillates (petroleum), hydrotreated middle)	Environmentally hazardous substance, liquid, n.o.s. (distillates (petroleum), hydrotreated middle)
<b>14.3 Transport hazard class(es)</b>	9 	9 	9 	9 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.

### Additional information

#### ADR/RID

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Hazard identification number** 90

**Tunnel code** (-)

#### ADN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

#### IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**Emergency schedules** F-A, S-F

#### IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

#### 14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Maritime transport in bulk according to IMO instruments

: Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

Marine Rubbing Pro

## SECTION 15: Regulatory information

### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not available.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

### Norway

**Product registration number** : 625085

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

*Marine Rubbing Pro***SECTION 15: Regulatory information****15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Aquatic Chronic 2, H411	Calculation method

**Full text of abbreviated H statements**

H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

**Full text of classifications [CLP/GHS]**

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

**Date of printing** : 24.03.2023**Date of issue/ Date of revision** : 24.03.2023**Date of previous issue** : 23.03.2023**Version** : 1.01

*Marine Rubbing Pro*

## **SECTION 16: Other information**

### **Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.